

Filter

The diesel filtration unit constitute an important guarantee to the protection of modern diesel motors that need cleaner motor fuel. The filter is mounted in suction or in delivery of the pump.



Code 7622
10 micron impurity filter and water separator

The main features of this filter are:

- separate and absorb water may be present in the diesel extracted.
- purify and decontaminate impurities in the fuel with a 10 micron capacity filter.

A reduction of the pump flow is due to its clogging that needs to be replaced.

Head with 1 "female.

Code 7632
Spare cartridge



Code 7620
30 micron impurity filter and water separator

The main features of this filter are:

- separate and absorb water may be present in the diesel extracted.
- purify and decontaminate impurities in the fuel with a 30 micron capacity filter.

A reduction of the pump flow is due to its clogging that needs to be replaced.

Head with 1 "female.

Code 7630
Spare cartridge



Cod. 7650
Cleaner Bio-Fuel

PureFuel Cleaner (PFC) A pre-filtration conditioner to reduce the effects of microbiological growth reduces filter blockage, fuel tank system corrosion and fuel injection problems.

Contamination of fuels, lubricating oils and hydraulic oils is now a common risk and causes extensive engine damage. THE BIOFUEL BLAST-FILLER fights microbial contamination and replaces the old and obsolete biocide chemical additive treatment practice. The installation of the BIOFUEL ABATTER increases the life of the fuel filters by 10 or more times, eliminates the blockage, prevents the formation of algae and reduces damage to the fuel tank coverings.

Pure fuel conditioner must be installed in a suction pump and before the unit filter.

Connections 1" female.

