

# Tanks for diesel fuel depots without box fuel dispensing unit

*Tanks serving thermal plants or generating sets.*

## TANK

with cylindrical horizontal axle fitted on anti-roll support brackets. Manufactured with top quality carbon steel S235JR UNI EN10025, submerged arc welded. Painted with epoxy powders, hydraulically tested and equipped of the following accessories: manhole diameter 420 mm with bolt and seals, 3" lockable rapid coupling ring-nut, with load-limiting valve calibrated at 90% of the tank geometric capacity, 1"-1/2 pressure relief valve with flame-breaker mesh. Externally visible level gauge with inner protection hose for the float, stair of access to the load (only for CD50, CD60, CD90), drain sleeve with ball valve on the bottom by 3/4" and security cap, eyebolts, plug grounding and equipotentiality.

Connection for fuel diesel suction:

1 nipple 1 "

2 sleeves female 1 "



## CONTAINMENT BASIN

made of carbon steel sheet, self-supporting base frame already preset and bolted to the bottom of the tank, it can be placed on any type of ground, **with a capacity of not less than 110% of the overall geometric capacity.** Equipped with safety cap 1" suitable for fixing the uprights of the roofing. The basin is entirely painted with epoxy powder.

Code	Capacity (litres)	Dimensions (without roof) (WxDxH mm)
CD5/B5110%	500	1200x1200x1300
CD10/B10110%	1000	1500x2000x1500
CD15/B15110%	1500	1500x2450x1500
CD23/B23110%	2300	1800x2450x1650
CD30/B30110%	3000	2100x2450x1800
CD50/B50110%	5000	2400x3200x2000
CD60/B60110%	6000	2400x3200x2200
CD90/B90110%	9000	2400x3900x2300