

Polyethylene wheeled tanks for diesel and Gasoline

Ideal for refueling small operating vehicles and light or recreational vehicles.

Manual rotary vane pump with manual nozzle and 3 m of delivery hose.



Code	Capacity (Litres)	Weight Kg.	Pump	Dimensions (mm)
TR55	55	9	manual	460x360x900 h
TR110	110	15	manual	460x440x1100 h
TR55D	55	9	manual	460x360x900 h
TR110D	110	15	manual	460x440x1100 h

DIESEL

Code TR55D

Wheeled diesel tank 55 litres.

Code TR110D

Wheeled diesel tank 110 litres.


GASOLINE

Code TR55

Wheeled gasoline tank 55 litres.

Code TR110

Wheeled gasoline tank 110 litres.



Combined polyethylene tank for transport and distributing diesel fuel and AUS 32

Dotazioni:

- Pump 12 VDC, 40 lt/min for Diesel compartment.
- Submersible pump 12 VDC 15 lt/min for Aus 32 compartment.
- 4 m delivery hose with automatic nozzle for Diesel.
- 4 m delivery hose with manual nozzle for Aus 32.
- 4 m electric cables with clamps for connection to the battery
- level indicator (only diesel compartment).

General characteristics:

- Capacity Diesel compartment: 400 l
- Capacity Aus 32 compartment: 50 l
- Dimensions: 1200 x 800 x 785 h mm
- Dimensions (version Pick-up): 1200 x 800 x H 830 mm
- Empty weight with transfer units 12V: 57 Kg
- Wall thickness: 6,5 mm.



DIESEL

+

AUS32



Code TC400D50U

Combined Tank for Diesel and Aus 32

Code TC400D50UPK

Combined Tank for Diesel and Aus 32 shaped for pick-up vehicles