

Tank for waste oil



A modern equipment for recovery and the storage of waste oils



TANK with cylindrical horizontal axle, fitted on anti-roll support brackets. Manufactured with top quality carbon steel S 235 JR UNI EN 10025, submerged arc welded. Painted with epoxy powders, hydraulically tested and equipped of the following accessories: manhole diameter 420 mm with bolt and seals, hatch locking, load compartment/ unloading oil filters with grill, 1"-1/2 pressure relief valve with flame-breaker mesh. Externally visible level gauge with inner protection hose for the float, drain sleeve with ball valve on the bottom by 3/4" and security cap, eyebolts.

CONTAINMENT BASIN made of carbon steel sheet, self-supporting base frame already preset and bolted to the bottom of the tank, it can be placed on any type of ground, **with a capacity of not less than 100% of the overall geometric capacity.** Equipped with safety cap 1" suitable for fixing the uprights of the roofing. The basin is entirely painted with epoxy powder



Code	Capacity (litres)	Dimension (without roof) (LxPxH mm)
SE1000	1000	1200x2000x1000
SE1500	1500	1400x2350x1200
SE2300	2300	1500x2450x1350



Code 545010
Kit Self loading pump



Code 545020
Kit self loading pump with basin wheeled oil drain

- Basin wheeled oil drain capacity: 70 litres
- Tank dimension: 800x560x180 mm

