

Hose

GREASE HIGH PRESSURE hose oil-resistant rubber, reinforced with 2 steel braids.
Operating pressure: 400 bar

DIAMETER 1/4"
(internal Ø 6,3 mm)

code	length (m)	connections
7090	0,5	M-M 10X1
7100	1	M-M 10X1
7105	1,5	M-M 10X1
7110	2	M-M 10X1
7115	2	F-F 1/4"
7018	4	F-F 1/4"
7020	6	F-F 1/4"
7030	8	F-F 1/4"
7040	10	F-F 1/4"
7050	12	F-F 1/4"

DIAMETER 5/16"
(internal Ø 8 mm)

code	length (m)	connections
7060	15	F-F 1/4"
7075	20	F-F 1/4"
7080	25	F-F 1/4"



OIL HIGH PRESSURE hose, oil-resistant rubber, reinforced with 1 steel braids.
Operating pressure: 160 bar

DIAMETER 1/2"
(internal Ø 12,7 mm)

code	length (m)	connections
7120	2	F-F 1/2"
7130	4	M-F 1/2"
7140	6	M-F 1/2"
7150	8	M-F 1/2"
7160	10	M-F 1/2"
7170	12	M-F 1/2"

DIAMETER 5/8"
(internal Ø 16 mm)

code	length (m)	connections
7180	15	M-F 1/2"
7188	20	M-F 1/2"
7189	25	M-F 1/2"



WASHER rubber hose, diam. 5/16", 400 bar, 100 °C, 3/8" M-F connection.

code	length (m)
7017I	3
7060I	15
7075I	20
7080I	25
7081I	30

